

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 July 2003 (24.07.2003)


PCT

(10) International Publication Number
WO 03/061344 A2

- (51) International Patent Classification⁷: **H04S 1/00** (74) Agent: **GROENENDAAL, Antonius, W., M.**; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (21) International Application Number: **PCT/IB02/05271**
- (22) International Filing Date: 9 December 2002 (09.12.2002) (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 02075198.8 17 January 2002 (17.01.2002) EP
- (71) Applicant (*for all designated States except US*): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): **SCHOBSEN, Daniel, W., E.** [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **EGELMEERS, Gerardus, P., M.** [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: MULTICHANNEL ECHO CANCELLER SYSTEM USING ACTIVE AUDIO MATRIX COEFFICIENTS



(57) Abstract: An echo canceller system is described, which comprises an audio matrix decoder coupled to audio inputs for providing multiple audio output signals, and a multi-channel echo canceller coupled to the audio inputs. The echo canceller system further comprises audio receiving means for receiving a mixture of the audio output signals and a wanted signal. The multi-channel echo canceller is coupled to the audio matrix decoder for using the audio matrix coefficients with multi-channel echo cancellation for deriving the wanted signal from the mixture. The computational and audio processing complexity of such a system is reduced.